Ordering information for GTF 112-Ex ... Probes

GTF 112-Ex- [ ] [ ][ ] [ ] [ ][ ] [ ] [ ][ ][ ] [ ] [ ][ ][ ][ ]

Protection type:

e	Gas: increased safety, encapsulation (em) - only permitted for zone 1 and 2
	Dust: encapsulation (mb) - only permitted for zone 21 and 22
i	intrinsic safety

Potentially explosive atmospheres:

Gases:

00	zone 0	
0A	zone 0/1	probe tube in zone 0 and cable sleeve in zone 1
01	zone 1 and zone 2	

Dusts:

20	zone 20	
2A	zone 20/21	probe tube in zone 20 and cable sleeve in zone 21
21	zone 21 and zone 22	

Sensor-element:

P	Pt100
T	Pt1000

Size of screw thread:

			Comment
00	without thread		*not suitable for zone isolation !*
11	G 1/8"	G-screw thread	*not suitable for zone isolation !*
12	G 1/4"		*only with D = 6 mm suitable for zone isolation !*
13	G 3/8"		
14	G 1/2"		
15	G 3/4"		
22	M10x1	M-screw thread	*not suitable for zone isolation !*
23	M12x1.5		*only with D = 6 mm suitable for zone isolation !*
24	M14x1.5		
25	M16x1.5		
26	M18x1.5		

other threads (e.g. NPT) on request

Neck tube:

K	without neck tube (for -50 °C ≤ T ≤ 100 °C)
M	with neck tube (please refer to note below)

Neck tube length:

xxx length in mm
e.g. 050 (= standard length)

Probe tube diameter:

x 3, 4, 5, 6 or 8 mm

Hint:
- for zone 0/1, 20/21 (= zone isolation) only 6 mm or 8 mm available
- observe for D = 3 mm:
  - minimum probe length is 60 mm
  - the probe diameter is reduced, tube top D = 3 mm (for approx. 30 mm) after this D = 6 mm

Probe length (fitting length):

xxxx length in mm
e.g. 0100 (= 100 mm)

Notify for ambient temperature:

intrinsic safety type	
zone 0, 20:	-20 °C ... +60 °C
zone 0/1, 1, 2:	-20 °C ... +80 °C (+60 °C bei T6)
zone 20/21, 21, 22:	-20 °C ... +80 °C (+60 °C bei T<100°C)
type with increased safety	
zone 1, 2, 21, 22:	-20 °C ... +60 °C

Recommended min. neck tube length according max. meas. range:

Neck tube construction:	measuring range: Pt 100	Pt 1000
- without neck tube	-250 … +100 °C	-50 … +100 °C
- neck tube above 50 mm	-200 … +250 °C	-70 … +250 °C
- neck tube above 100 mm	-200 … +400 °C	-70 … +400 °C
- neck tube above 200 mm	-200 … +600 °C	-70 … +600 °C

For reference only! The length should be selected so that the max. specified ambient temperature of the cable sleeve is not exceeded in your installation situation.

Ordering example: **GTF 112-Ex** for protection type "i", Ex-zone 1, with Pt100, thread: G 1/2", neck tube length: 50 mm, probe diameter: 6 mm, probe length: 200 mm

GTF 112-Ex- [i] [0][1] [P] [1][6] [M] [0][5][0] [6] [0][2][0][0]

GHM GROUP - Greisinger
GHM Messtechnik GmbH | Hans-Sachs-Str. 26 | 93128 Regenstauf | GERMANY
Tel.: +49 9402 9383-0 | Fax.: +49 9402 9383-33
http://www.greisinger.de | info@greisinger.de